

# Medium Pressure

#### HOK 65/80 1CT

Medium Pressure Mercury lamps are available in a wide range with an arc length between 10 and 140 centimeter. The lamps can be fitted with various types of end fitting from our catalogue, or equipped with customer special fittings, cables or pins. The lamps are made from selected types of quartz glass, with transmission characteristics tailored to the application. Medium Pressure Mercury lamps contain sophisticated quantities of mercury bromides, providing a self-cleaning halogen cycle, to control the depreciation of UV radiation over lamp life.

#### Product data

#### • General Characteristics

Cap-Base SK32
Cap-Base Information Execution Operating Position p10
Main Application Industrial UV
Run Time 0.083 (max) hr

• Electrical Characteristics

Lamp Wattage 5000 W Lamp Wattage Tech- 5000 W

nical

Lamp Voltage 780 (min), 840 (nom), 900 (max) V

Lamp Current 6.6 A Ignition Time 10 (max) s Re-ignition Time 10 (max) min Consumed Watt per 80 W/cm

cm

### • Product Dimensions

Overall Length C 716 (max) mm Diameter D 24 (max) mm Arc Length O 650 mm

#### • Luminaire Design Requirements

Pinch Temperature 300 (max) C Bulb Temperature 600 (min), 900 (max) C

#### • Product Data

Order code 928188605104
Full product code 928188605104
Full product name Order product name Pieces per pack 928188605104
HOK 65/80 1CT/4
1

Pieces per pack 1
Packing configuration 4
Packs per outerbox 4

Bar code on pack - 8711500188670

EAN1

Bar code on outerbox - EAN3

8711500188687

928188605104

Logistic code(s) - 12NC

Net weight per piece 0.225 kg




# Medium Pressure

# Dimensional drawing







Product	C (Max)	D (Max)	O (Norm)
HOK 65/80	738	21.92	650



## **Medium Pressure**

### Photometric data







Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.