



MSD Platinum (Touring/Stage)

MSD Platinum 5 R 1CT/8

The MSD Platinum lamps open up new levels of creative freedom in entertainment lighting, with powerful, compact and brilliantly intense light. Their compact, lightweight design provides the freedom to create smaller, lighter luminaires – for use at any location on stage. And their short arc, high color temperature and innovative reflector produce a sparkling, high beam intensity for outstanding color reproduction. They also offer long and reliable lifetime, high efficacy and fast replacement times. It all adds up to an intensely exciting creative experience.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General information		Correlated Color Temperature (Nom)		8000 K
Cap-Base	- [-]	Color Rendering Index (Nom)		-
Operating Position	UNIVERSAL [Any or Universal (U)]	Operating and electrical		
Main Application	Stage/Touring	Power (Nom)	189 W	
Life to 50% Failures (Nom)	3000 h	Controls and dimming		
System Description	Reflector-E20.6	Dimmable	Yes	
Light technical		Mechanical and housing		
Color Code	2	Cap-Base Information	-	
Luminous Flux (Min)	7100 lm			
Luminous Flux (Nom)	7950 lm			
Chromaticity Coordinate X (Nom)	300			
Chromaticity Coordinate Y (Nom)	300			

MSD Platinum (Touring/Stage)

Luminaire design requirements


Pinch Temperature (Max)	350 °C
Pinch Temperature (Max)-DUP(do not use)	350 °C

Product data

Full product code	872790093070200
Order product name	MSD Platinum 5 R 1CT/8
EAN/UPC - Product	8727900930702

Order code	928190805314
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	8
Material Nr. (12NC)	928190805314
Net Weight (Piece)	0.120 kg

Dimensional drawing



MSD Platinum 5 R 1CT/8

Product	D (max)	T (max)	O	C (max)
MSD Platinum 5 R 1CT/8	51.4 mm	6.8 mm	1.0 mm	57.1 mm

Photometric data

